



Apollo



120
Shield



180
Python



320
Sunlight



510
Enlighten



515
Bronze



530
Wreath



545
**New England
Blackbutt**



555
**Grafton
Spotted Gum**



570
**Western
Blackbutt**



625
Tallowood



710
Oracle



730
Dolphin



While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice.
*Subject to proper installation, maintenance and local building code/regulatory approval.

Apollo

Apollo captures the natural beauty of timber with the best attributes of a laminate and vinyl flooring. The innovative Hybrid flooring delivers astonishing durability and impact resistance. With Trigon® core technology and a scratch resistance surface this beautiful and durable floor is able to withstand heavy foot traffic.

Technical Data

Type	Hybrid	Finish	Matte
Plank Thickness	5.8mm	Surface	Embossed
Wear Layer	0.3mm	Top Layer	Decorative Film & Wear Layer
Dimensions	1220mm (L) x 180mm (W)	Substrate Layer	Trigon® Core Technology (Limestone Composite)
Planks per Box	10	Backing Layer	1.5mm EVA
M² per Box	2.196m ²	Profile	Micro Bevel
M² per Pallet	131.76m ²	Protective Coating	UV Coating
Colours	12		
Installation Method	Drop Lock		

Performance

Dimensional Stability	Length: 0.05% Width: -0.05% Curling: 0.00%	ISO 23999														
Thermal Resistance	0.061m ² .K/w	EN 12667														
Thermal Conductivity	0.101 W/(m.K)	EN 12667														
Abrasion Rating	Group T	EN 660-2														
Swelling After Submersion in Water	0.1%	ISO 24336														
Impact Sound Reduction	<table border="1"> <thead> <tr> <th>Test Application</th> <th>Ln'T,w</th> <th>Result</th> </tr> </thead> <tbody> <tr> <td>150mm Slab + 28mm Furrings + 10mm Plasterboard</td> <td>51</td> <td rowspan="5">ISO140-7 / ISO717.2</td> </tr> <tr> <td>200m Slab</td> <td>55</td> </tr> <tr> <td>200mm Slab + 28mm Furrings + 10mm Plasterboard</td> <td>50</td> </tr> <tr> <td>200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard</td> <td>47</td> </tr> <tr> <td>250mm Slab + 28mm Furrings + 10mm Plasterboard</td> <td>49</td> </tr> </tbody> </table>	Test Application	Ln'T,w	Result	150mm Slab + 28mm Furrings + 10mm Plasterboard	51	ISO140-7 / ISO717.2	200m Slab	55	200mm Slab + 28mm Furrings + 10mm Plasterboard	50	200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard	47	250mm Slab + 28mm Furrings + 10mm Plasterboard	49	
Test Application	Ln'T,w	Result														
150mm Slab + 28mm Furrings + 10mm Plasterboard	51	ISO140-7 / ISO717.2														
200m Slab	55															
200mm Slab + 28mm Furrings + 10mm Plasterboard	50															
200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard	47															
250mm Slab + 28mm Furrings + 10mm Plasterboard	49															
Light Fastness	Grade 6	EN ISO 105-B02														
Fire Classification	CRF 10.6kW/m ² Smoke Value 92% minutes	ISO 9239														
Slip Resistance	P3	AS 4586														
Residential Warranty*	15 Year Hybrid Limited Residential Warranty															
Commercial Warranty†	3 Year Commercial Warranty available upon request															

Sustainability

VOC Rating	Passes CETEC VOC test
Global GreenTag	GreenRate Level A certified



Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. All Godfrey Hirst Hybrid Floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Floors Installation Instructions. *This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com. †Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.